

K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

HANSA FLEX

Caracteristici

| | |
|--------------------------------|--|
| Curent de lucru | 200 mA |
| Îmbinare cablu prin înșurubare | M 20 x 1.5 |
| Funcție de comutare | Positive switching, PNP NO contact, damped or undamped in the end position |
| Tip de protecție | IP 67, acc. to DIN EN 60529 |
| Domeniu de temperaturi | -20 °C to +70 °C |
| Carcasă | Polyamide blue or black |
| Șurub | Stainless steel 1.4301 |
| Arbore | Polyamide PA6, black |
| Capac | Polycarbonate, transparent |
| Punte de montaj | PA6 with 30 % glass fibre |
| Garnituri | EPDM and NBR |
| Material de etanșare | NBR |



Indicație

Alte date sunt disponibile la cerere.

Descriere

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Articol

| Denumire | Tensiune | Definiție |
|----------------|---------------|---|
| K- 07 30 29 06 | 9 V - 36 V DC | End position feedback, D 2 type with inductive 3-wire sensors |