


K-MV O (NO) D 24 V DC H

Normally open, (NO), directly operated, 24 V DC, for high pressures

HANSA FLEX

Caracteristici

Conexiune electrică	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Tip de protecție	IP 65
Temperatură mediu	max. 80 °C when using water or oils; max. 90 °C when using with air
Descriere filet	G thread acc. DIN EN ISO 228-1
Carcasă, scaun al supapei	Brass
Piese interioare	Stainless steel
Garnitură de etanșare	FPM



Indicație

Alte date sunt disponibile la cerere.

Descriere

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Articol

Denumire	Filet	presiune max. de lucru (bar)	NW	A (mm)	B (mm)	C (mm)	Forma constructivă
K- 07 30 01 90	G 1/8	20	1,5	70,0	40,0	76,0	2
K- 07 30 01 91	G 1/4	20	1,5	70,0	40,0	76,0	2
K- 07 30 01 92	G 3/8	20	3,0	85,0	52,0	92,0	2
K- 07 30 01 93	G 1/2	20	3,0	85,0	52,0	92,0	2