


# K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

**HANSA FLEX**

## Caracteristici

Presiune de lucru	Max. 6 bar (copper alloy), Max. 25 bar (stainless steel)
Ø guler de etanșare	26 mm
Ø tub de protecție	10 mm
Material	Copper alloy, CrNi-Steel 1.4571



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

For bimetallic thermometers in the »High quality« series.

## Articol

Denumire	Filet de conectare	Lungime de montare	SW (mm)	Material
K- 07 20 11 35	G 1/2	L1 = 63 mm	27	Copper alloy
K- 07 20 11 36	G 1/2	L1 = 100 mm	27	Copper alloy
K- 07 20 11 37	G 1/2	L1 = 160 mm	27	Copper alloy
K- 07 20 11 38	G 1/2	L1 = 63 mm	27	CrNi steel 1.4571
K- 07 20 11 39	G 1/2	L1 = 100 mm	27	CrNi steel 1.4571
K- 07 20 11 40	G 1/2	L1 = 160 mm	27	CrNi steel 1.4571

## Accesorii

K-BIMETALLTHERMOMETER 52-2 Bimetallic thermometers