


K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

HANSA FLEX

Caracteristici

Presiune de lucru	Max. 12 bar, maximum static working pressure (non-pulsating)
Presiune de lucru manșoane conectabile și nipluri	0 to 35 bar
Debit aer	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-20 °C to +60 °C
Carcasă, corp al supapei	Nickel-plated brass
Supapă	Brass
Manșon de deblocare	Plastic
Arc, inel elastic, știfturi, bile	Stainless steel
Material de etanșare	NBR



Indicație

Alte date sunt disponibile la cerere.

Descriere

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 03 04	Stem, I.D. 6	71,2	22
K- 07 35 03 05	Stem, I.D. 8	71,2	22
K- 07 35 03 06	Stem, I.D. 9	71,2	22
K- 07 35 03 07	Stem, I.D. 10	71,2	22
K- 07 35 03 08	Stem, I.D. 13	71,2	22

Elemente adiționale

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,