## K-TR POLYURETHAN

Polyurethane hose (PUR)



Caracteristici				
Presiune de lucru	Max. 10 bar (at +20 °C)			
Duritate	52 Shore D±3			
Calibrare	External			
Temperatură ambientală	-35 °C to +80 °C			
Material	Poliuretan			



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

This externally calibrated plastic hose made of high-quality polyester PUR is extremely flexible with optimal mechanical characteristics and very high pressure resistance across a wide temperature range. It is permanently flexible, boasts very good resilience and can be laid with a narrow bending radius. Its other advantages include good abrasion resistance, very good low-temperature flexibility and very high elongation at break. The hose is also suitable for vacuum applications. It is resistant to many different oils and lubricants (a special resistance test is recommended in specific cases owing to the additives that are blended in by the manufacturers), aliphatic hydrocarbons and gases such as oxygen, ozone, helium, etc.

Articol						
Denumire	Ø furtun interior	Ø furtun exterior	Rază de îndoire relevantă pentru debit (mm)	Culoarea	Lungimea rolelor	
K- 07 10 05 47	2,6	4,0	17	Natural	25	
K- 07 10 05 49	3,1	5,0	15	Natural	100	
K- 07 10 05 48	3,1	5,0	15	albastru	100	
K- 07 10 05 51	9,0	12,0	67	Natural	100	
K- 07 10 05 52	9,0	12,0	67	negru	100	
K- 07 10 05 54	9,8	14,0	72	Natural	50	
K- 07 10 05 53	9,8	14,0	72	albastru	50	
K- 07 10 05 55	9,8	14,0	72	negru	50	
K- 07 10 05 56	11,0	16,0	88	Natural	50	
K- 07 10 05 57	11,0	16,0	88	negru	50	