
## K-ZFL ABSP-KLAPPEN EINFACH

Butterfly valves, with single-acting actuator - spring to close, min. pilot pressure 5 bar



Pneumatic actuators, in double- or single acting version
Max. 16 bar
-15 °C to +120 °C
Water / steam, salt water, salt water, ester, ketone, alkali, caustic soda, sodium hydroxide. Not recommended for hydrocarbons
5.5 bar
Supplied as standard, operated by a 3/2- or 5/2-way valve
90 °
aluminium eloxed
NBR
Grey cast iron GG25 epoxy resin coated, RAL 5015
EPDM
SS416
EPDM



## Indicație

Alte date sunt disponibile la cerere.

Articol								
Denumire	Şaibă	DN	B (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L (mm)	
K- 07 30 03 36	Stainless Steel CF8M/1.4404	40	38,0	68,0	108,0	238,0	94,0	
K- 07 30 03 37	Stainless Steel CF8M/1.4404	50	47,0	71,0	143,0	273,0	100,0	
K- 07 30 03 38	Stainless Steel CF8M/1.4404	65	49,0	78,0	155,0	285,0	115,0	
K- 07 30 03 39	Stainless Steel CF8M/1.4404	80	47,0	89,0	162,0	292,0	127,0	
K- 07 30 03 40	Stainless Steel CF8M/1.4404	100	56,0	102,0	178,0	348,0	163,0	
K- 07 30 03 42	Stainless Steel CF8M/1.4404	125	59,0	123,0	191,0	361,0	190,0	
K- 07 30 03 44	Stainless Steel CF8M/1.4404	150	59,0	138,0	265,0	395,0	216,0	