# K-W45 120 IG IG

Elbows 120, 45°, female/female

## Caracteristici

| | |
|---|---|
| **Suprafaţă** | Hot dip galvanised |
| **Domeniu de temperaturi** | -20 °C to +300 °C (at 20 bar) |
| **Filet de conectare** | acc. ISO 7-1 |
| **Material** | Black malleable iron B350-10, design symbol A |
| **Aprobare** | DIN DVGW |



## Indicaţie

Alte date sunt disponibile la cerere.

## Descriere

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

## Informaţii suplimentare

Further types and dimensions on request.

## Articol

| Denumire | Filet |
|---|---|
| **K- 07 40 38 37** | Rp 3/8 |
| **K- 07 40 38 34** | Rp 1/2 |
| **K- 07 40 38 36** | Rp 3/4 |
| **K- 07 40 38 31** | Rp 1 |
| **K- 07 40 38 33** | Rp 1 1/4 |
| **K- 07 40 38 32** | Rp 1 1/2 |
| **K- 07 40 38 35** | Rp 2 |
| **K- 07 40 52 68** | Rp 2 1/2 |
| **K- 07 40 52 69** | Rp 3 |

*În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.*