

# K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface

**HANSA FLEX**

## Caracteristici

Medii	Air, neutral gases (filtered)
Presiune de lucru	1.5 - 8 bar
Temperatura de lucru	+5 °C to +50 °C
Conexiune electrică	Plug connector PG 9
Carcasă	Aluminium
Material de etanșare	NBR



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

## Articol

Denumire	Tensiune	Port 1	Conexiunea 3 + 5	DN	Debit (L/min)
K- 07 15 00 09	230 V, 50 Hz	G 1/4	G 1/4	8	1370
K- 07 15 00 10	24 V DC	G 1/4	G 1/4	8	1370
K- 07 15 00 11	230 V, 50 Hz	G 3/8	G 1/4	10	1650
K- 07 15 00 12	24 V DC	G 3/8	G 1/4	10	1650