


K-T AG-K ISO 7-1 2 VA

Male branch tees, conical male thread acc. to ISO 7-1, stainless steel

HANSA FLEX

Caracteristici

Domeniu de presiune	Max. 25 bar
furtunuri recomandate	PTFE hose
Domeniu de temperaturi	-40 °C to +200 °C (depending on the hose quality and diameter)
Material	Oțel superior 1.4404
Garnitură de etanșare	Pure metal



Indicație

Alte date sunt disponibile la cerere.

Descriere

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Articol

Denumire	Filet	pentru furtun	L1 (mm)	L2 (mm)	Deschiderea cheii 1 (mm)	Deschiderea cheii 2 (mm)
K- 07 40 30 43	R 1/8	6 mm / 4 mm	46,0	17,0	12	10
K- 07 40 30 44	R 1/8	8 mm / 6 mm	46,0	17,0	14	10
K- 07 40 30 41	R 1/4	6 mm / 4 mm	46,0	21,5	12	10
K- 07 40 30 42	R 1/4	8 mm / 6 mm	46,0	21,5	14	10
K- 07 40 30 40	R 1/4	10 mm / 8 mm	52,0	21,5	16	12