
# K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

## Caracteristici

| | |
|---|---|
| **Medii** | Air, neutral gases, filtered |
| **Presiune de lucru** | 1.5 to 10 bar |
| **Temperatura de lucru** | -20 °C to +70 °C |
| **Conexiune electrică** | Plug connector PG 9 |
| **Cuprins în pachetul de livrare** | Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws |
| **Putere absorbită** | 3 W=/5 VA~ |
| **Carcasă** | Aluminium, anodised |
| **Vană** | Stainless steel |
| **Material de etanșare** | NBR |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.
Two or three-piece service units with excellent flow rates in modern design. <br>Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.<br>

## Articol

| Denumire | Tensiune | Racord | DN | Debit (L/min) |
|---|---|---|---|---|
| **K- 07 15 00 05** | 230 V, 50 Hz | G 1/4 | 7 | 1250 |
| **K- 07 15 00 06** | 24 V DC | G 1/4 | 7 | 1250 |

*În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.*