

# K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

**HANSA FLEX**

## Caracteristici

Medii	Air, neutral gases, filtered
Presiune de lucru	1.5 to 10 bar
Temperatura de lucru	-20 °C to +70 °C
Conexiune electrică	Plug connector PG 9
Cuprins în pachetul de livrare	Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws
Putere absorbită	3 W=5 VA~
Carcasă	Aluminium, anodised
Vană	Stainless steel
Material de etanșare	NBR



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design. <br>Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.<br>

## Articol

Denumire	Tensiune	Racord	DN	Debit (L/min)
K- 07 15 00 05	230 V, 50 Hz	G 1/4	7	1250
K- 07 15 00 06	24 V DC	G 1/4	7	1250