K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

Caracteristici

Medii	Air, neutral gases, filtered
Presiune de lucru	0.5 to 10 bar
Temperatura de lucru	-20 °C to +70 °C
Cuprins în pachetul de livrare	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
Carcasă	Aluminium, anodised
Material	Garnitură: NBR
Material de etanşare	NBR



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Articol

Denumire	Funcţia	Acţionare	DN	Debit (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650

În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.