K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

Caracteristici

Medii	Filtered, unlubricated compressed air
Presiune de lucru	2.5 - 8 bar
Domeniu de temperaturi	-10 °C to +60 °C
Racord	Push-in fitting for pipe 4 mm
Acționare	Pneumatic
Debit aer 6 bari	85 Nl/min
Decalaj max. semnal de intrare	0,4 s



Indicație

Alte date sunt disponibile la cerere.

Descriere

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter.Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Articol

Denumire	Definiție	Racord
K- 07 15 26 09	Two-hand safety valve without housing	Push-in fitting for 4 mm pipe
K- 07 15 26 10	mounting element	-

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.