

K-LKM S NW7,8 AG

Safety couplings DN 7.8, male

HANSA FLEX

Caracteristici

Presiune de lucru	max. 20 bari
Debit aer	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-20 °C to +100 °C
Racord corp al supapei	Nickel-plated brass
Arc, bile	Stainless-steel
Mașon culisant	Anodised aluminium
Mașon de deblocare	Hardened and nickel-plated steel
Material de etanșare	NBR



Indicație

Alte date sunt disponibile la cerere.

Descriere

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 08 82	R 1/4 male	80,0	19
K- 07 35 08 83	R 3/8 male	81,0	19
K- 07 35 08 84	R 1/2 male	87,0	22

Elemente adiționale

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass