

K-SVKM NW 7,2 DREH MS-NI

Quick disconnect couplings DN 7.2, nickel-plated brass, swivel type

HANSA FLEX

Caracteristici

Presiune de lucru	0 - 35 bar, maximum static working pressure (non-pulsating)
Debit aer	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	0 °C to +70 °C
Carcasă, manșon	Nickel-plated brass
Supapă	Brass with a bare metal surface
Arc, inel elastic	Stainless steel 1.4310
Știfturi de blocare	Stainless steel 1.4034
Material de etanșare	NBR



Indicație

Alte date sunt disponibile la cerere.

Descriere

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Articol

Denumire	Racord	Lungime (mm)
K- 07 35 07 28	Stem 6 mm, swivel type	74,0
K- 07 35 07 29	Stem 8 mm, swivel type	74,0
K- 07 35 07 30	Stem 9 mm, swivel type	74,0
K- 07 35 07 31	Stem, 10 mm, swivel type	74,0
K- 07 35 07 32	Stem, 13 mm, swivel type	74,0

Elemente adiționale

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass