

# K-SVKM NW 7,6 IG ST

Quick disconnect couplings DN 7.6, galvanised steel / nickel-plated brass, female

**HANSA FLEX**

## Caracteristici

Presiune de lucru	Max. 16 bar
Debit aer	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-20 °C to +100 °C
Carcasă	Steel
Arc	Stainless-steel
Manșon culisant	Hardened and nickel-plated steel
Material de etanșare	NBR



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

## Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 07 80	G 1/4 female	57,0	20
K- 07 35 07 81	G 3/8 female	60,0	22
K- 07 35 07 82	G 1/2 female	60,0	25

## Elemente adiționale

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel