


K-SVKM NW 7,8 IG VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, female

HANSA FLEX

Caracteristici

Presiune de lucru	0 - 35 bar, maximum static working pressure (non-pulsating)
Debit aer	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-15 °C to +200 °C
Carcasă, manșon, corp al supapei	Stainless steel 1.4305
Arc, inel elastic, bile	Stainless steel
Material de etanșare	FKM



Indicație

Alte date sunt disponibile la cerere.

Descriere

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 07 93	G 1/4 female	55,5	19
K- 07 35 07 94	G 3/8 female	54,5	19
K- 07 35 07 95	G 1/2 female	57,5	24

Elemente adiționale

K-NIPPEL KUPPL NW7 AG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 1	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305