


# K-NIPPEL KUPPL NW7 AG VA 1

Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male

**HANSA FLEX**

## Caracteristici

|                   |   |
|-------------------|---|
| Presiune de lucru | max. 10 bari                                  |
| Debit aer         | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| Material          | stainless steel 1.4305                        |



## Articol

| Denumire       | Definiție       | SW<br>(mm) |
|----------------|-----------------|------------|
| K- 07 35 02 63 | Plug G 1/8 male | 14         |
| K- 07 35 02 64 | Plug G 1/4 male | 17         |
| K- 07 35 02 65 | Plug G 3/8 male | 19         |
| K- 07 35 02 66 | Plug G 1/2 male | 24         |

## este element adițional la următoarele produse

|                           |   |
|---------------------------|---|
| K-SVKM NW 7,8 AG VA       | Quick disconnect couplings DN 7.8, stainless steel 1.4305, male           |
| K-SVKM NW 7,8 IG VA       | Quick disconnect couplings DN 7.8, stainless steel 1.4305, female         |
| K-SVKM NW 7,8 SCHL TUE VA | Quick disconnect couplings DN 7.8, stainless steel 1.4305, with hose stem |