

# K-WV 5/2 EINS PNEU

5/2-way spool valves, single pneumatic

## Caracteristici

| | |
|---|---|
| **Funcţie** | 5/2-way |
| **Presiune de lucru** | 2.5 - 10 bar; Max. vacuum 10 bar (external pilot air) |
| **Presiune de lucru min.** | 2,5 bar |
| **Domeniu de temperaturi** | -10 °C to +60 °C |
| **Debit 6 bari şi 10 bari** | 1500 Nl/min (G 1/4), 4600 Nl/min (G 1/2) |
| **Conexiune electrică** | Coupler plug PG 9 - form B |
| **Tip de protecţie** | IP 65 (DIN 46244) |
| **Carcasă** | Anodised aluminium, blue |
| **Sertar cilindric** | Stainless steel |
| **Material de etanşare** | NBR |






## Indicaţie

Alte date sunt disponibile la cerere.

## Descriere

This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality. <br>The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems. <br>Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

## Articol

| Denumire | Racord | DN | Număr schemă electrică | Comandă |
|---|---|---|---|---|
| **K- 07 15 02 17** | G 1/4 | 8 | 27 | |
| **K- 07 15 02 18** | G 1/2" | 15 | 27 | |

*În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.*