

K-SVKM NW 5 SCHL UEM MS NI

Quick disconnect couplings DN 5, nickel-plated brass with hose connector, swivel nut and kink protector spring

HANSA FLEX

Caracteristici

| | |
|----------------------------------|---|
| Presiune de lucru | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Debit aer | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatură mediu | -20 °C to +100 °C |
| Carcasă, manșon, corp al supapei | Nickel-plated brass |
| Arc, inel elastic, bile | Stainless steel |
| Material de etanșare | NBR |



Indicație

Alte date sunt disponibile la cerere.

Descriere

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Articol

| Denumire | Racord | Execuție | Lungime (mm) | SW (mm) |
|----------------|-----------------------|-----------------|--------------|---------|
| K- 07 35 06 67 | Hose connection 6 x 4 | Rigid | 120,0 | 14 |
| K- 07 35 06 68 | Hose connection 8 x 6 | Rigid | 132,0 | 14 |
| K- 07 35 06 69 | Hose connection 6 x 4 | Swivelling 360° | 134,0 | 14 |
| K- 07 35 06 70 | Hose connection 8 x 6 | Swivelling 360° | 142,5 | 14 |