

K-T-STECK VERS DRE MINI PAR

Male branch tees, swivel type, mini, parallel thread

HANSA FLEX

Caracteristici

Presiune de lucru	Max. 10 bar, vacuum
Domeniul de utilizare	Air, vacuum
furtunuri recomandate	PU or PA (nylon)
Medii	Aer comprimat
Standard	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
Domeniu de temperaturi	0 °C to +60 °C
Suprafață de etanșare	O-ring (NBR)
Material	Plastic, Nickel plated brass
Inel de presiune	Plastic



Indicație

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

Articol

Denumire	Filet	pentru Ø exterior furtun	L1 (mm)	L2 (mm)	Deschiderea cheii fixe
K- 07 40 23 04	M 3	3 mm	24,0	16,0	8 mm
K- 07 40 23 05	M 3	4 mm	28,0	17,2	8 mm
K- 07 40 23 06	M 5	3 mm	24,0	16,0	8 mm
K- 07 40 23 07	M 5	4 mm	28,0	17,2	8 mm
K- 07 40 23 08	M 5	6 mm	32,0	18,2	8 mm
K- 07 40 23 09	M 6	3 mm	24,0	16,5	10 mm
K- 07 40 23 10	M 6	4 mm	28,0	17,6	10 mm
K- 07 40 23 11	M 6	6 mm	32,0	18,6	10 mm
K- 07 40 23 12	G 1/8	4 mm	28,0	16,5	14 mm
K- 07 40 23 13	G 1/8	6 mm	32,0	16,5	14 mm
K- 07 40 23 14	R 1/8	4 mm	28,0	18,0	10 mm
K- 07 40 23 15	R 1/8	6 mm	32,0	19,0	10 mm