# K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

## Caracteristici

| | |
|---|---|
| **Medii** | Air, neutral gases (filtered) |
| **Presiune de lucru** | 1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22) |
| **Temperatura de lucru** | -20 °C to +50 °C |
| **Racord 1 - 3** | G 1/4 (Port 1), G 1/4 (Port 3 and 5) |
| **Racord 1/3 + 5** | G 1/4 (Port 1), G 1/4 (Port 3 and 5) |
| **Conexiune electrică** | Plug connector PG 9 |
| **Cuprins în pachetul de livrare** | Plug connector PG 9, conversion plate, screws and seal |
| **Putere absorbită** | 3 W=/5 VA~ |
| **Carcasă** | Anodised aluminium |
| **Vană** | Stainless steel |
| **Material de etanşare** | NBR |



## Indicaţie

Alte date sunt disponibile la cerere.

## Descriere

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.
Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## Articol

| Denumire | Tensiune | Port 1 | Conexiunea 3 + 5 | DN | Debit (L/min) |
|---|---|---|---|---|---|
| **K- 07 15 00 13** | 230 V, 50 Hz | G 1/4 | G 1/4 | 7 | 1250 |
| **K- 07 15 00 14** | 24 V DC | G 1/4 | G 1/4 | 7 | 1250 |

*În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.*