K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continous thread



| Caracteristici | |
|--------------------|---------------------|
| Presiune de lucru | Max. 50 bar |
| Filet de conectare | acc. ISO 7-1 |
| Material | black steel ST 37-2 |



Indicație

Alte date sunt disponibile la cerere.

Descriere

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. they are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

| Articol | | | |
|----------------|---------|-----------------|--|
| Denumire | Filet | Lungime (mm) | |
| K- 07 40 35 30 | R 1/4 | 25,0 | |
| K- 07 40 35 33 | R 3/8 | 26,0 | |
| K- 07 40 35 29 | R 1/2 | 34,0 | |
| K- 07 40 35 32 | R 3/4 | 36,0 | |
| K- 07 40 35 26 | R 1 | 43,0 | |
| K- 07 40 35 28 | R 1 1/4 | 48,0 | |
| K- 07 40 35 27 | R 1 1/2 | 48,0 | |
| K- 07 40 35 31 | R 2 | 56,0 | |
| K- 07 40 50 36 | R 2 1/2 | 65,0 | |
| K- 07 40 50 37 | R 3 | 71,0 | |