

# K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continuous thread

**HANSA****FLEX**

## Caracteristici

|                    |                     |
|--------------------|---------------------|
| Presiune de lucru  | Max. 50 bar         |
| Filet de conectare | acc. ISO 7-1        |
| Material           | black steel ST 37-2 |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

## Articol

| Denumire      | Filet   | Lungime (mm) |
|---------------|---------|--------------|
| K-07 40 35 30 | R 1/4   | 25,0         |
| K-07 40 35 33 | R 3/8   | 26,0         |
| K-07 40 35 29 | R 1/2   | 34,0         |
| K-07 40 35 32 | R 3/4   | 36,0         |
| K-07 40 35 26 | R 1     | 43,0         |
| K-07 40 35 28 | R 1 1/4 | 48,0         |
| K-07 40 35 27 | R 1 1/2 | 48,0         |
| K-07 40 35 31 | R 2     | 56,0         |
| K-07 40 50 36 | R 2 1/2 | 65,0         |
| K-07 40 50 37 | R 3     | 71,0         |