

K-S-BKR M ENTL-BOHR ABSCHL

Safety ball valves, lockable, with relief port

HANSA FLEX

Caracteristici

| | |
|-----------------------|--|
| Temperatura de lucru | -10 °C to + 100 °C (depending on operating pressure) |
| Orificiu de dezaerare | M 5 (>1"): Relief port G 1/4" |
| Descriere filet | Rp thread acc. to EN 10226 |
| Carcasă | Nickel-plated brass |
| Manetă | Steel - PVC coated |
| Rulment | hardchrome-plated brass |
| Etanșare bilă | PTFE |
| Etanșare ax | PTFE |



Indicație

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Alte date sunt disponibile la cerere.

Descriere

2/2-way safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications. The valve shuts off the supply line and bleeds the application area. Lockable hand lever in closed position.

Informații suplimentare

The price does not include a padlock. Please order separately.

Articol

| Denumire | DN | Filet | PN (bar) | A (mm) | B (mm) | L (mm) |
|----------------|----|----------|----------|--------|--------|--------|
| K- 07 30 29 29 | 8 | Rp 1/4 | 14 | 96,0 | 49,0 | 45,0 |
| K- 07 30 29 30 | 10 | Rp 3/8 | 14 | 96,0 | 49,0 | 45,0 |
| K- 07 30 29 31 | 15 | Rp 1/2 | 14 | 96,0 | 51,0 | 59,0 |
| K- 07 30 29 32 | 20 | Rp 3/4 | 14 | 117,0 | 60,0 | 64,0 |
| K- 07 30 29 33 | 25 | Rp 1 | 14 | 117,0 | 64,0 | 81,0 |
| K- 07 30 29 34 | 32 | Rp 1 1/4 | 14 | 157,0 | 80,0 | 93,0 |
| K- 07 30 29 35 | 40 | Rp 1 1/2 | 14 | 157,0 | 86,0 | 102,0 |
| K- 07 30 29 36 | 50 | Rp 2 | 14 | 157,0 | 93,0 | 121,0 |

Accesorii

K-VORHAENGESCHLOSS Padlock