

K-ZWEIHAND S KONSOLE KOMPL

Complete pushbutton panel

HANSA FLEX

Caracteristici

| | |
|--------------------------------|---------------------------------------|
| Medii | Filtered, unlubricated compressed air |
| Presiune de lucru | 2.5 - 8 bar |
| Domeniu de temperaturi | -10 °C to +60 °C |
| Racord | Push-in fitting for pipe 4 mm |
| Aționare | Pneumatic |
| Debit aer 6 bari | 85 NI/min |
| Decalaj max. semnal de intrare | 0,4 s |



Indicație

Alte date sunt disponibile la cerere.

Descriere

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Articol

| Denumire | Definiție |
|----------------|---|
| K- 07 15 26 08 | Complete pushbutton panel with safety valve |