

# K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

**HANSA FLEX**

## Caracteristici

Presiune de lucru	Max. 50 bar
Suprafață	Hot dip galvanised
Filet de conectare	acc. ISO 7-1
Material	Zinc plated steel ST 37-2



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

## Articol

Denumire	Filet	Lungime (mm)
K- 07 40 35 71	R 1/4	40,0
K- 07 40 35 72	R 1/4	60,0
K- 07 40 35 73	R 1/4	80,0
K- 07 40 35 66	R 1/4	100,0
K- 07 40 35 67	R 1/4	120,0
K- 07 40 35 68	R 1/4	150,0
K- 07 40 35 69	R 1/4	180,0
K- 07 40 35 70	R 1/4	200,0
K- 07 40 35 95	R 3/8	40,0
K- 07 40 35 96	R 3/8	60,0
K- 07 40 35 97	R 3/8	80,0
K- 07 40 35 90	R 3/8	100,0
K- 07 40 35 91	R 3/8	120,0
K- 07 40 35 92	R 3/8	150,0
K- 07 40 35 93	R 3/8	180,0
K- 07 40 35 94	R 3/8	200,0
K- 07 40 35 63	R 1/2	40,0
K- 07 40 35 64	R 1/2	60,0
K- 07 40 35 65	R 1/2	80,0
K- 07 40 35 58	R 1/2	100,0
K- 07 40 35 59	R 1/2	120,0
K- 07 40 35 60	R 1/2	150,0
K- 07 40 35 61	R 1/2	180,0
K- 07 40 35 62	R 1/2	200,0
K- 07 40 35 87	R 3/4	40,0
K- 07 40 35 88	R 3/4	60,0
K- 07 40 35 89	R 3/4	80,0
K- 07 40 35 82	R 3/4	100,0
K- 07 40 35 83	R 3/4	120,0
K- 07 40 35 84	R 3/4	150,0
K- 07 40 35 85	R 3/4	180,0
K- 07 40 35 86	R 3/4	200,0
K- 07 40 35 39	R 1	40,0
K- 07 40 35 40	R 1	60,0
K- 07 40 35 41	R 1	80,0
K- 07 40 35 34	R 1	100,0
K- 07 40 35 35	R 1	120,0
K- 07 40 35 36	R 1	150,0



În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.

25.04.2026

HANSA-FLEX AG

www.hansa-flex.com

1

# K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

**HANSA FLEX**

## Articol

Denumire	Filet	Lungime (mm)
K- 07 40 35 37	R 1	180,0
K- 07 40 35 38	R 1	200,0
K- 07 40 35 55	R 1 1/4	40,0
K- 07 40 35 56	R 1 1/4	60,0
K- 07 40 35 57	R 1 1/4	80,0
K- 07 40 35 50	R 1 1/4	100,0
K- 07 40 35 51	R 1 1/4	120,0
K- 07 40 35 52	R 1 1/4	150,0
K- 07 40 35 53	R 1 1/4	180,0
K- 07 40 35 54	R 1 1/4	200,0
K- 07 40 35 47	R 1 1/2	40,0
K- 07 40 35 48	R 1 1/2	60,0
K- 07 40 35 49	R 1 1/2	80,0
K- 07 40 35 42	R 1 1/2	100,0
K- 07 40 35 43	R 1 1/2	120,0
K- 07 40 35 44	R 1 1/2	150,0
K- 07 40 35 45	R 1 1/2	180,0
K- 07 40 35 46	R 1 1/2	200,0
K- 07 40 35 79	R 2	40,0
K- 07 40 35 80	R 2	60,0
K- 07 40 35 81	R 2	80,0
K- 07 40 35 74	R 2	100,0
K- 07 40 35 75	R 2	120,0
K- 07 40 35 76	R 2	150,0
K- 07 40 35 77	R 2	180,0
K- 07 40 35 78	R 2	200,0
K- 07 40 50 93	R 2 1/2	80,0
K- 07 40 50 88	R 2 1/2	100,0
K- 07 40 50 89	R 2 1/2	120,0
K- 07 40 50 90	R 2 1/2	150,0
K- 07 40 50 91	R 2 1/2	180,0
K- 07 40 50 92	R 2 1/2	200,0
K- 07 40 50 99	R 3	80,0
K- 07 40 50 94	R 3	100,0
K- 07 40 50 95	R 3	120,0
K- 07 40 50 96	R 3	150,0
K- 07 40 50 97	R 3	180,0
K- 07 40 50 98	R 3	200,0