

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Caracteristici

Presiune de lucru	Max. 50 bar
Suprafață	Hot dip galvanised
Filet de conectare	acc. ISO 7-1
Material	Zinc plated steel ST 37-2



Indicație

Alte date sunt disponibile la cerere.

Descriere

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Articol

Denumire	Filet	Lungime (mm)
K- 07 40 35 71	R 1/4	40,0
K- 07 40 35 72	R 1/4	60,0
K- 07 40 35 73	R 1/4	80,0
K- 07 40 35 66	R 1/4	100,0
K- 07 40 35 67	R 1/4	120,0
K- 07 40 35 68	R 1/4	150,0
K- 07 40 35 69	R 1/4	180,0
K- 07 40 35 70	R 1/4	200,0
K- 07 40 35 95	R 3/8	40,0
K- 07 40 35 96	R 3/8	60,0
K- 07 40 35 97	R 3/8	80,0
K- 07 40 35 90	R 3/8	100,0
K- 07 40 35 91	R 3/8	120,0
K- 07 40 35 92	R 3/8	150,0
K- 07 40 35 93	R 3/8	180,0
K- 07 40 35 94	R 3/8	200,0
K- 07 40 35 63	R 1/2	40,0
K- 07 40 35 64	R 1/2	60,0
K- 07 40 35 65	R 1/2	80,0
K- 07 40 35 58	R 1/2	100,0
K- 07 40 35 59	R 1/2	120,0
K- 07 40 35 60	R 1/2	150,0
K- 07 40 35 61	R 1/2	180,0
K- 07 40 35 62	R 1/2	200,0
K- 07 40 35 87	R 3/4	40,0
K- 07 40 35 88	R 3/4	60,0
K- 07 40 35 89	R 3/4	80,0
K- 07 40 35 82	R 3/4	100,0
K- 07 40 35 83	R 3/4	120,0
K- 07 40 35 84	R 3/4	150,0
K- 07 40 35 85	R 3/4	180,0
K- 07 40 35 86	R 3/4	200,0
K- 07 40 35 39	R 1	40,0
K- 07 40 35 40	R 1	60,0
K- 07 40 35 41	R 1	80,0
K- 07 40 35 34	R 1	100,0
K- 07 40 35 35	R 1	120,0
K- 07 40 35 36	R 1	150,0



În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.

28.05.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982



Articol

Denumire	Filet	Lungime (mm)
K- 07 40 35 37	R 1	180,0
K- 07 40 35 38	R 1	200,0
K- 07 40 35 55	R 1 1/4	40,0
K- 07 40 35 56	R 1 1/4	60,0
K- 07 40 35 57	R 1 1/4	80,0
K- 07 40 35 50	R 1 1/4	100,0
K- 07 40 35 51	R 1 1/4	120,0
K- 07 40 35 52	R 1 1/4	150,0
K- 07 40 35 53	R 1 1/4	180,0
K- 07 40 35 54	R 1 1/4	200,0
K- 07 40 35 47	R 1 1/2	40,0
K- 07 40 35 48	R 1 1/2	60,0
K- 07 40 35 49	R 1 1/2	80,0
K- 07 40 35 42	R 1 1/2	100,0
K- 07 40 35 43	R 1 1/2	120,0
K- 07 40 35 44	R 1 1/2	150,0
K- 07 40 35 45	R 1 1/2	180,0
K- 07 40 35 46	R 1 1/2	200,0
K- 07 40 35 79	R 2	40,0
K- 07 40 35 80	R 2	60,0
K- 07 40 35 81	R 2	80,0
K- 07 40 35 74	R 2	100,0
K- 07 40 35 75	R 2	120,0
K- 07 40 35 76	R 2	150,0
K- 07 40 35 77	R 2	180,0
K- 07 40 35 78	R 2	200,0
K- 07 40 50 93	R 2 1/2	80,0
K- 07 40 50 88	R 2 1/2	100,0
K- 07 40 50 89	R 2 1/2	120,0
K- 07 40 50 90	R 2 1/2	150,0
K- 07 40 50 91	R 2 1/2	180,0
K- 07 40 50 92	R 2 1/2	200,0
K- 07 40 50 99	R 3	80,0
K- 07 40 50 94	R 3	100,0
K- 07 40 50 95	R 3	120,0
K- 07 40 50 96	R 3	150,0
K- 07 40 50 97	R 3	180,0
K- 07 40 50 98	R 3	200,0