

K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

HANSA FLEX

Caracteristici

Tip	233.30
Execuție	Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Utilizare	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
Clasă de calitate	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Temperatură mediu	max. +100 °C
Temperatură ambiantă	-20 °C până la +60 °C
Carcasă	CrNi steel
Fereastră de vizitare	Laminated safety glass Ø 63 = Polycarbonate



Indicație

Alte date sunt disponibile la cerere.

Articol

Denumire	Domeniu de măsurare	Ø (mm)	Racord
K- 07 20 07 03	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 04	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 05	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 06	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 07	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 08	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 09	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 10	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 11	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 07 12	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 07 13	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 07 14	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 01 79	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 80	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 81	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 82	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 83	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 84	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 85	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 86	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 87	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 88	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 89	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 90	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 91	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 92	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 93	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 94	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 95	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 96	0 - 600.0 bar	100,0	G 1/2"