

# K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

**HANSA FLEX**

## Caracteristici

|                       |   |
|-----------------------|---|
| Tip                   | 233.30  |
| Execuție              | Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)     |
| Utilizare             | For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere |
| Clasă de calitate     | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm)   |
| Temperatură mediu     | max. +100 °C  |
| Temperatură ambiantă  | -20 °C până la +60 °C   |
| Carcasă               | CrNi steel  |
| Fereastră de vizitare | Laminated safety glass Ø 63 = Polycarbonate   |



## Indicație

Alte date sunt disponibile la cerere.

## Articol

| Denumire       | Domeniu de măsurare | Ø<br>(mm) | Racord |
|----------------|---------------------|-----------|--------|
| K- 07 20 07 03 | -1 / 0.0 bar        | 63,0      | G 1/4" |
| K- 07 20 07 04 | 0 - 4.0 bar         | 63,0      | G 1/4" |
| K- 07 20 07 05 | 0 - 6.0 bar         | 63,0      | G 1/4" |
| K- 07 20 07 06 | 0 - 10.0 bar        | 63,0      | G 1/4" |
| K- 07 20 07 07 | 0 - 16.0 bar        | 63,0      | G 1/4" |
| K- 07 20 07 08 | 0 - 25.0 bar        | 63,0      | G 1/4" |
| K- 07 20 07 09 | 0 - 40.0 bar        | 63,0      | G 1/4" |
| K- 07 20 07 10 | 0 - 60.0 bar        | 63,0      | G 1/4" |
| K- 07 20 07 11 | 0 - 100.0 bar       | 63,0      | G 1/4" |
| K- 07 20 07 12 | 0 - 160.0 bar       | 63,0      | G 1/4" |
| K- 07 20 07 13 | 0 - 250.0 bar       | 63,0      | G 1/4" |
| K- 07 20 07 14 | 0 - 400.0 bar       | 63,0      | G 1/4" |
| K- 07 20 01 79 | -1 / 0.0 bar        | 100,0     | G 1/2" |
| K- 07 20 01 80 | -1 / +1.5 bar       | 100,0     | G 1/2" |
| K- 07 20 01 81 | -1 / +3.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 82 | -1 / +5.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 83 | -1 / +9.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 84 | 0 - 2.5 bar         | 100,0     | G 1/2" |
| K- 07 20 01 85 | 0 - 4.0 bar         | 100,0     | G 1/2" |
| K- 07 20 01 86 | 0 - 6.0 bar         | 100,0     | G 1/2" |
| K- 07 20 01 87 | 0 - 10.0 bar        | 100,0     | G 1/2" |
| K- 07 20 01 88 | 0 - 16.0 bar        | 100,0     | G 1/2" |
| K- 07 20 01 89 | 0 - 25.0 bar        | 100,0     | G 1/2" |
| K- 07 20 01 90 | 0 - 40.0 bar        | 100,0     | G 1/2" |
| K- 07 20 01 91 | 0 - 60.0 bar        | 100,0     | G 1/2" |
| K- 07 20 01 92 | 0 - 100.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 93 | 0 - 160.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 94 | 0 - 250.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 95 | 0 - 400.0 bar       | 100,0     | G 1/2" |
| K- 07 20 01 96 | 0 - 600.0 bar       | 100,0     | G 1/2" |