

K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

HANSA FLEX

Caracteristici

Presiune de lucru	max. 10 bari
Debit aer	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatură mediu	-20 °C to +150 °C
Carcasă	Stainless steel 1.4404
Filet	Stainless steel 1.4404
Piese interioare	Stainless steel 1.4404
Buton, supapă	Stainless steel 1.4404
Material de etanșare	FKM



Indicație

Not suitable for hitting / pulsating tools.

Alte date sunt disponibile la cerere.

Descriere

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Informații suplimentare

Not suitable for hitting / pulsating tools.

Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24