

K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

HANSA **FLEX**

Caracteristici

| | |
|----------------------|---|
| Presiune de lucru | max. 10 bari |
| Debit aer | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| Temperatură mediu | -20 °C to +150 °C |
| Carcasă | Stainless steel 1.4404 |
| Filet | Stainless steel 1.4404 |
| Piese interioare | Stainless steel 1.4404 |
| Buton, supapă | Stainless steel 1.4404 |
| Material de etanșare | FKM |



Indicație

Not suitable for hitting / pulsating tools.

Alte date sunt disponibile la cerere.

Descriere

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Informații suplimentare

Not suitable for hitting / pulsating tools.

Articol

| Denumire | Racord | Lungime (mm) | SW (mm) |
|----------------|--------------|--------------|---------|
| K- 07 35 12 79 | G 1/4 female | 71,5 | 21 |
| K- 07 35 12 80 | G 3/8 female | 75,5 | 21 |
| K- 07 35 12 81 | G 1/2 female | 77,5 | 24 |