


# K-FI REGL PC-BEHAELTER S MAN VARIOB

Filter regulators with polycarbonate bowl, bowl guard and pressure gauge

**HANSA****FLEX**

## Caracteristici

Presiune de intrare	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Temperatură mediu	max. 50 °C
Temperatură ambientală	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Mărimea porilor în elementul filtrant	40 µm
Material de etanșare	NBR
Apărătoare de arc	POM
Carcasă	Die-cast zinc
Membrană	NBR
Drain valve	Manual
Măsurarea valorii debitului	At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the knob down. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

## Indicații referitoare comandă

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## Informații suplimentare

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## Articol

Denumire	Filet	Domeniu de reglare	Debit (L/min)	A (mm)	B	C (mm)
K-07 25 23 01	G 1/4	0.5 - 10 bar	2000	48,0	203,0 mm	68,0
K-07 25 23 00	G 3/8	0.5 - 10 bar	3000	48,0	203,0 mm	68,0
K-07 25 22 99	G 1/2	0.5 - 10 bar	5500	70,0	273,0 mm	98,0
K-07 25 22 98	G 3/4	0.5 - 10 bar	6500	70,0	273,0 mm	98,0
K-07 25 22 97	G 1	0.5 - 10 bar	6500	124,0	273,0 mm	98,0