K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick diconnect couplings and stems DN 7.2

Caracteristici

Strat interior	Soft-PVC, black
Inserţie	Împletitură din poliester
Strat exterior	Soft-PVC, blue
Temperatura de lucru	-20 °C to +60 °C



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Highly flexible hose for compressed air applications in workshop areas. Assembled wit brass stem and brass quick disconnect coupling DN 7.2

Articol

Denumire	Ø furtun interior (mm)	Ø furtun exterior (mm)	Presiune de lucru max. la 20°C (bar)	Lungime furtun (m)
K- 07 10 11 91	6,3	11,0	15	5
K- 07 10 11 85	6,3	11,0	15	10
K- 07 10 11 87	6,3	11,0	15	15
K- 07 10 11 88	6,3	11,0	15	20
K- 07 10 11 90	6,3	11,0	15	25
K- 07 10 11 99	9,0	14,5	15	5
K- 07 10 11 93	9,0	14,5	15	10
K- 07 10 11 95	9,0	14,5	15	15
K- 07 10 11 96	9,0	14,5	15	20
K- 07 10 11 98	9,0	14,5	15	25

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.