

K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick disconnect couplings and stems DN 7.2

HANSA FLEX

Caracteristici

Strat interior Soft-PVC, black

Insertie Împletitură din poliester

Strat exterior Soft-PVC, blue

Temperatura de lucru -20 °C to +60 °C



Indicație

Alte date sunt disponibile la cerere.

Descriere

Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2

Articol

Denumire	Ø furtun interior (mm)	Ø furtun exterior (mm)	Presiune de lucru max. la 20°C (bar)	Lungime furtun (m)
K- 07 10 11 91	6,3	11,0	15	5
K- 07 10 11 85	6,3	11,0	15	10
K- 07 10 11 87	6,3	11,0	15	15
K- 07 10 11 88	6,3	11,0	15	20
K- 07 10 11 90	6,3	11,0	15	25
K- 07 10 11 99	9,0	14,5	15	5
K- 07 10 11 93	9,0	14,5	15	10
K- 07 10 11 95	9,0	14,5	15	15
K- 07 10 11 96	9,0	14,5	15	20
K- 07 10 11 98	9,0	14,5	15	25