

K-SOFT PVC SET SVKM TUE NW7,4

Soft PVC workshop hose kit with mounted pushbutton safety coupling
DN 7.4 and nickel-plated brass stem

HANSA FLEX

Caracteristici

Strat interior Soft-PVC, black

Insertie Împletitură din poliester

Strat exterior Soft-PVC, blue

Temperatura de lucru -20 °C to +60 °C



Indicație

Alte date sunt disponibile la cerere.

Descriere

Highly flexible hose for compressed air applications in workshop areas. Assembled with pushbutton safety coupling DN 7.4

Nu este adecvat pentru unelte cu percuție sau cu pulsații!

Articol

| Denumire | Ø furtun interior (mm) | Ø furtun exterior (mm) | Presiune de lucru max. la 20°C (bar) | Lungime furtun (m) |
|----------------|---------------------------|---------------------------|---|-----------------------|
| K- 07 10 11 92 | 6,3 | 11,0 | 12 | 5 |
| K- 07 10 11 86 | 6,3 | 11,0 | 12 | 10 |
| K- 07 10 11 89 | 6,3 | 11,0 | 12 | 20 |
| K- 07 10 12 00 | 9,0 | 14,5 | 12 | 5 |
| K- 07 10 11 94 | 9,0 | 14,5 | 12 | 10 |
| K- 07 10 11 97 | 9,0 | 14,5 | 12 | 20 |