

K-L-STECKVER AG-K

Male elbows, conical male thread

HANSA FLEX

Caracteristici

| | |
|----------------------|------------------|
| Presiune de lucru | Max. 16 bar |
| Temperatura de lucru | -20 °C to +80 °C |
| Material | Alamă nichelată |
| Inel de presiune | Hostaform |
| Inel de prindere | Stainless steel |



Indicație

Alte date sunt disponibile la cerere.

Descriere

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Articol

| Denumire | Filet | pentru Ø exterior furtun | L1 (mm) | L2 (mm) | Deschiderea cheii fixe |
|----------------|-------|--------------------------|------------|------------|------------------------|
| K- 07 40 25 65 | R 1/8 | 4 mm | 18,6 | 16,0 | 10 mm |
| K- 07 40 25 66 | R 1/8 | 6 mm | 21,9 | 16,0 | 10 mm |
| K- 07 40 25 67 | R 1/8 | 8 mm | 25,4 | 16,0 | 10 mm |
| K- 07 40 25 63 | R 1/4 | 6 mm | 21,9 | 18,5 | 10 mm |
| K- 07 40 25 64 | R 1/4 | 8 mm | 25,4 | 18,5 | 10 mm |
| K- 07 40 25 62 | R 1/4 | 10 mm | 27,2 | 22,0 | 14 mm |