

K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media, nonlinearity 0.2%

HANSA FLEX

Caracteristici

Tip	S-11
Tensiune	DC 10 (14) ... 30 V
Conexiune electrică	With right-angle connector acc. to DIN EN 175301-803 A
Tip de protecție	IP 65 acc. to EN 60529
Semnal de ieșire	4 to 20 mA, 2-wire
Neliniaritate	0.2% of span
Temperatură mediu	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Temperatură ambientală	-20 °C to +80 °C
Părți care vin în contact cu substanța de măsurare	CrNi steel 1.4571
Carcasă	CrNi steel 1.4571



Descriere

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Informații suplimentare

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Articol

Denumire	Domeniu de măsurare	Filet
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Piese de schimb

K-ZUBEH DRUCKMESSUMFOR Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%