

# K-STECKVERSCHR AGR-K SK BESCH

Male connectors, conical male thread, coated with outer hex

**HANSA FLEX**

## Caracteristici

|                      |                     |
|----------------------|---------------------|
| Presiune de lucru    | Max. 16 bar         |
| Temperatura de lucru | -20 °C to +150 °C   |
| Material             | Alamă nichelată     |
| Inel de presiune     | Nickel-plated brass |
| Inel de prindere     | Stainless steel     |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Articol

| Denumire       | Filet | pentru Ø exterior furtun | L1<br>(mm) | Deschiderea cheii fixe |
|----------------|-------|--------------------------|------------|------------------------|
| K- 07 40 27 26 | R 1/8 | 4 mm                     | 22,5       | 10 mm                  |
| K- 07 40 27 27 | R 1/8 | 6 mm                     | 24,5       | 11 mm                  |
| K- 07 40 27 28 | R 1/8 | 8 mm                     | 27,5       | 13 mm                  |
| K- 07 40 47 62 | R 1/4 | 4 mm                     | 22,5       | 14 mm                  |
| K- 07 40 27 24 | R 1/4 | 6 mm                     | 24,5       | 14 mm                  |
| K- 07 40 27 25 | R 1/4 | 8 mm                     | 27,5       | 13 mm                  |
| K- 07 40 27 23 | R 1/4 | 10 mm                    | 32,5       | 16 mm                  |
| K- 07 40 47 61 | R 1/4 | 12 mm                    | 32,5       | 17 mm                  |
| K- 07 40 27 30 | R 3/8 | 8 mm                     | 28,0       | 17 mm                  |
| K- 07 40 27 29 | R 3/8 | 10 mm                    | 32,5       | 17 mm                  |
| K- 07 40 47 63 | R 3/8 | 12 mm                    | 30,5       | 17 mm                  |
| K- 07 40 47 60 | R 1/2 | 12 mm                    | 33,0       | 22 mm                  |