

K-STECKVERBINDU RED 10BAR

Reducers (pressure max. 10 bar)

HANSA FLEX

Caracteristici

| | |
|------------------------|--|
| Presiune de lucru | Max. 10 bar |
| Domeniul de utilizare | Air, vacuum |
| furtunuri recomandate | PU or PA (nylon) |
| Medii | Compressed air and all gases or liquids that are compatible with the materials |
| Domeniu de temperaturi | -20 °C to +80 °C |
| Material | Plastic, Nickel plated brass |
| Inel de presiune | Plastic |



Indicație

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Articol

| Denumire | pentru Ø exterior furtun | L1 (mm) |
|----------------|--------------------------|------------|
| K- 07 40 03 45 | 6 mm / 4 mm | 31,0 |
| K- 07 40 41 34 | 8 mm / 4 mm | 36,5 |
| K- 07 40 03 46 | 8 mm / 6 mm | 34,5 |
| K- 07 40 41 35 | 10 mm / 6 mm | 40,2 |
| K- 07 40 03 47 | 10 mm / 8 mm | 39,4 |
| K- 07 40 41 36 | 12 mm / 8 mm | 45,0 |
| K- 07 40 03 48 | 12 mm / 10 mm | 44,2 |
| K- 07 40 03 49 | 16 mm / 12 mm | 49,6 |