


K-L-STECKVER SK DREH AG-K

Banjo elbows with outer hex, swivel type, conical male thread, coated



Caracteristici	
Presiune de lucru	Max. 15 bar, coarse vacuum
Domeniul de utilizare	Air, vacuum
furtunuri recomandate	PU or PA (nylon)
Medii	Compressed air and all gases or liquids that are compatible with the materials
Domeniu de temperaturi	-20 °C to +80 °C
Suprafață de etanșare	Conical version: thread coating
Material	Plastic, Nickel plated brass
Inel de presiune	Plastic



Indicație

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Articol					
Denumire	Filet	pentru Ø exterior furtun	L1 (mm)	L2 (mm)	Deschiderea cheii fixe
K- 07 40 09 52	R 1/8	4 mm	22,3	23,5	10 mm
K- 07 40 09 53	R 1/8	6 mm	22,9	23,5	10 mm
K- 07 40 09 54	R 1/8	8 mm	25,3	23,5	10 mm
K- 07 40 09 50	R 1/4	6 mm	24,9	26,3	14 mm
K- 07 40 09 51	R 1/4	8 mm	28,4	26,3	14 mm
K- 07 40 09 49	R 1/4	10 mm	32,0	26,3	14 mm
K- 07 40 43 51	R 1/4	12 mm	33,2	26,3	14 mm
K- 07 40 09 57	R 3/8	6 mm	26,6	31,9	19 mm
K- 07 40 09 58	R 3/8	8 mm	29,3	31,9	19 mm
K- 07 40 09 55	R 3/8	10 mm	32,5	31,9	19 mm
K- 07 40 09 56	R 3/8	12 mm	35,3	31,9	19 mm
K- 07 40 09 48	R 1/2	8 mm	32,3	38,6	24 mm
K- 07 40 09 46	R 1/2	10 mm	35,5	38,6	24 mm
K- 07 40 09 47	R 1/2	12 mm	36,3	38,6	24 mm