


# K-SCHOTT-STECKVERB IG-K

Male bulkhead connectors, conical female thread

## Caracteristici

<b>Presiune de lucru</b>	Max. 15 bar, coarse vacuum
<b>Domeniul de utilizare</b>	Air, vacuum
<b>furtunuri recomandate</b>	PU or PA (nylon)
<b>Medii</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Domeniu de temperaturi</b>	-20 °C to +80 °C
<b>Suprafață de etanșare</b>	Conical version: thread coating
<b>Material</b>	Plastic, Nickel plated brass
<b>Inel de presiune</b>	Plastic



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Articol

Denumire	Filet	pentru Ø exterior furtun	Filet tablou de comandă	L1 (mm)	Deschiderea cheii fixe
K- 07 40 04 42	Rc 1/8	4 mm	M 12 x 1	23,8	14 mm
K- 07 40 04 43	Rc 1/8	6 mm	M 14 x 1	27,0	17 mm
K- 07 40 04 44	Rc 1/8	8 mm	M 16 x 1	32,1	19 mm
K- 07 40 04 40	Rc 1/4	6 mm	M 14 x 1	30,0	17 mm
K- 07 40 04 41	Rc 1/4	8 mm	M 16 x 1	35,1	19 mm
K- 07 40 04 38	Rc 1/4	10 mm	M 20 x 1	36,0	24 mm
K- 07 40 04 39	Rc 1/4	12 mm	M 22 x 1	38,1	24 mm
K- 07 40 04 45	Rc 3/8	10 mm	M 20 x 1	37,0	24 mm
K- 07 40 04 46	Rc 3/8	12 mm	M 22 x 1	39,1	24 mm
K- 07 40 04 37	Rc 1/2	12 mm	M 22 x 1	41,1	24 mm