

K-L-SCHOTT STECK

Bulkhead connectors, elbow type

HANSA FLEX

Caracteristici

| | |
|------------------------|--|
| Presiune de lucru | Max. 15 bar, coarse vacuum |
| Domeniul de utilizare | Air, vacuum |
| furtunuri recomandate | PU or PA (nylon) |
| Medii | Compressed air and all gases or liquids that are compatible with the materials |
| Domeniu de temperaturi | -20 °C to +80 °C |
| Material | Plastic, Nickel plated brass |
| Inel de presiune | Plastic |



Indicație

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Articol

| Denumire | pentru Ø exterior furtun | Filet tablou de comandă | L1 (mm) | L2 (mm) | Deschiderea cheii fixe |
|----------------|--------------------------|-------------------------|------------|------------|------------------------|
| K- 07 40 04 47 | 4 mm | M 12 x 1 | 17,5 | 31,3 | 14 mm |
| K- 07 40 04 48 | 6 mm | M 14 x 1 | 18,7 | 37,9 | 17 mm |
| K- 07 40 04 49 | 8 mm | M 16 x 1 | 22,5 | 43,6 | 19 mm |
| K- 07 40 04 50 | 10 mm | M 20 x 1 | 27,2 | 51,2 | 24 mm |
| K- 07 40 04 51 | 12 mm | M 22 x 1 | 29,3 | 56,1 | 27 mm |
| K- 07 40 04 52 | 16 mm | M 27 x 1 | 32,5 | 62,6 | 30 mm |