


# K-STECKVERSCH AGR OR SK M O 1

Male connectors, parallel male thread with O-ring and outer hex

**HANSA FLEX**

## Caracteristici

|                      |                     |
|----------------------|---------------------|
| Presiune de lucru    | Max. 16 bar         |
| Temperatura de lucru | -20 °C to +150 °C   |
| Material             | Alamă nichelată     |
| Inel de presiune     | Nickel-plated brass |
| Inel O               | FKM (FPM)           |
| Inel de prindere     | Stainless steel     |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Articol

| Denumire       | Filet | pentru Ø exterior furtun | L1 (mm) | Deschiderea cheii fixe |
|----------------|-------|--------------------------|---------|------------------------|
| K- 07 40 27 31 | M 5   | 4 mm                     | 20,5    | Ø 9 mm                 |
| K- 07 40 27 32 | M 5   | 6 mm                     | 22,5    | Ø 10,5 mm              |
| K- 07 40 27 38 | G 1/8 | 4 mm                     | 20,0    | 9 mm                   |
| K- 07 40 27 39 | G 1/8 | 6 mm                     | 24,0    | 11 mm                  |
| K- 07 40 27 40 | G 1/8 | 8 mm                     | 26,5    | 13 mm                  |
| K- 07 40 27 35 | G 1/4 | 4 mm                     | 21,0    | 9 mm                   |
| K- 07 40 47 67 | G 1/8 | 10 mm                    | 29,0    | 16 mm                  |
| K- 07 40 27 36 | G 1/4 | 6 mm                     | 24,0    | 11 mm                  |
| K- 07 40 27 37 | G 1/4 | 8 mm                     | 25,0    | 13 mm                  |
| K- 07 40 27 34 | G 1/4 | 10 mm                    | 29,0    | 16 mm                  |
| K- 07 40 47 66 | G 1/4 | 12 mm                    | 31,5    | 18 mm                  |
| K- 07 40 27 42 | G 3/8 | 8 mm                     | 25,0    | 13 mm                  |
| K- 07 40 27 41 | G 3/8 | 10 mm                    | 29,5    | 16 mm                  |
| K- 07 40 47 68 | G 3/8 | 12 mm                    | 31,0    | 18 mm                  |
| K- 07 40 47 69 | G 3/8 | 14 mm                    | 34,0    | 21 mm                  |
| K- 07 40 27 33 | G 1/2 | 10 mm                    | 31,0    | 16 mm                  |
| K- 07 40 47 64 | G 1/2 | 12 mm                    | 31,5    | 18 mm                  |
| K- 07 40 47 65 | G 1/2 | 14 mm                    | 34,5    | 21 mm                  |