



K-T-STECK VERS DRE AG OR

Male branch tees, swivel type, parallel male thread with O-ring

HANSA FLEX

Caracteristici

Presiune de lucru	Max. 16 bar
Temperatura de lucru	-20 °C to +150 °C
Material	Alamă nichelată
Inel de presiune	Nickel-plated brass
Inel O	FKM (FPM)
Inel de prindere	Stainless steel



Indicație

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Articol

Denumire	Filet	pentru Ø exterior furtun	L1 (mm)	L2 (mm)	Deschiderea cheii fixe
K- 07 40 27 80	G 1/8	4 mm	40,0	20,0	13 mm
K- 07 40 27 81	G 1/8	6 mm	43,0	20,0	13 mm
K- 07 40 27 82	G 1/8	8 mm	47,0	20,0	13 mm
K- 07 40 27 78	G 1/4	6 mm	43,0	24,0	13 mm
K- 07 40 27 79	G 1/4	8 mm	47,0	24,0	13 mm
K- 07 40 27 77	G 1/4	10 mm	53,0	24,0	16 mm
K- 07 40 27 84	G 3/8	8 mm	47,0	25,5	13 mm
K- 07 40 27 83	G 3/8	10 mm	53,0	28,0	16 mm
K- 07 40 47 89	G 3/8	12 mm	58,0	28,5	20 mm
K- 07 40 47 88	G 1/2	12 mm	58,0	33,5	20 mm