

K-Y-WINKELVERSCH DRE AG OR

Male branch Y-elbows with outer hex, swivel type, parallel male thread with O-ring

HANSA FLEX

Caracteristici

| | |
|------------------------|--|
| Presiune de lucru | Max. 15 bar, coarse vacuum |
| Domeniul de utilizare | Air, vacuum |
| furtunuri recomandate | PU or PA (nylon) |
| Medii | Compressed air and all gases or liquids that are compatible with the materials |
| Domeniu de temperaturi | -20 °C to +80 °C |
| Suprafață de etanșare | Parallel version: O-ring in housing |
| Material | Plastic, Nickel plated brass |
| Inel de presiune | Plastic |



Indicație

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Articol

| Denumire | Filet | pentru Ø exterior furtun | L1 (mm) | L2 (mm) | Deschiderea cheii fixe |
|----------------|-------|--------------------------|------------|------------|------------------------|
| K- 07 40 43 07 | M 5 | 4 mm | 24,0 | 22,0 | 12 mm |
| K- 07 40 43 10 | G 1/8 | 6 mm | 24,0 | 25,0 | 12 mm |
| K- 07 40 43 09 | G 1/4 | 8 mm | 28,5 | 28,8 | 14 mm |
| K- 07 40 43 11 | G 3/8 | 10 mm | 33,7 | 34,8 | 19 mm |
| K- 07 40 43 08 | G 1/2 | 12 mm | 37,5 | 42,1 | 24 mm |