

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Caracteristici

Strat interior Soft-PVC, black

Insertie Împletitură din poliester

Strat exterior Soft-PVC, blue

Temperatură -20 °C to +60 °C

Lungimea rolelor 50 m



Indicație

Alte date sunt disponibile la cerere.

Descriere

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Articol

Denumire	Ø furtun interior (mm)	Ø furtun exterior (mm)	Max. working pressure resistance at 23°C (bar)	Rază min. de îndoire (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88