K-WERKST-SCHLAUCH SOFT

Workshop hose soft

Caracteristici

Strat interior	Soft-PVC, black
Inserţie	Împletitură din poliester
Strat exterior	Soft-PVC, blue
Temperatură	-20 °C to +60 °C
Lungimea rolelor	50 m



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Articol

Denumire	Ø furtun interior (mm)	Ø furtun exterior (mm)	Max. working pressure resistance at 23°C (bar)	Rază min. de îndoire (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.