


# K-SCHOTT-STECKVERB RED

Female bulkhead connectors, unequal

**HANSA FLEX**

## Caracteristici

|                      |                  |
|----------------------|------------------|
| Presiune de lucru    | Max. 16 bar      |
| Temperatura de lucru | -20 °C to +80 °C |
| Material             | Alamă nichelată  |
| Inel de presiune     | Hostaform        |
| Inel de prindere     | Stainless steel  |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Articol

| Denumire       | Filet    | pentru Ø exterior furtun | L1<br>(mm) | Deschiderea cheii fixe |
|----------------|----------|--------------------------|------------|------------------------|
| K- 07 40 25 51 | M 13 x 1 | 4 mm / 6 mm              | 32,7       | 16 mm                  |
| K- 07 40 25 54 | M 15 x 1 | 4 mm / 8 mm              | 34,4       | 17 mm                  |
| K- 07 40 25 55 | M 15 x 1 | 6 mm / 8 mm              | 35,0       | 17 mm                  |
| K- 07 40 25 57 | M 17 x 1 | 6 mm / 10 mm             | 37,5       | 20 mm                  |
| K- 07 40 25 58 | M 17 x 1 | 8 mm / 10 mm             | 37,8       | 20 mm                  |
| K- 07 40 47 17 | M 20 x 1 | 10 mm / 12 mm            | 40,8       | 24 mm                  |
| K- 07 40 47 18 | M 20 x 1 | 6 mm / 12 mm             | 39,0       | 24 mm                  |
| K- 07 40 47 19 | M 20 x 1 | 8 mm / 12 mm             | 40,1       | 24 mm                  |