

# K-LKM S NW7,2 SCHL TUE

Safety couplings DN 7.2, with hose stem

**HANSA FLEX**

## Caracteristici

Presiune de lucru	0 - 35 bar, maximum static working pressure (non-pulsating)
Debit aer	1.100 l/min (at $\Delta p = 0.5$ bar)
Temperatură mediu	-30 °C to +100 °C
Carcasă, manșon, corp al supapei	Nickel-plated brass
Arc, bile	Stainless-steel
Material de etanșare	NBR



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

## Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 02 87	Stem, I.D. 6	60,0	22
K- 07 35 02 88	Stem, I.D. 8	60,0	22
K- 07 35 02 89	Stem, I.D. 9	60,0	22
K- 07 35 02 90	Stem, I.D. 10	60,0	22
K- 07 35 02 91	Stem, I.D. 13	60,0	22

## Elemente adiționale

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,